

# equipment

	30V4	35V4	45V4	55V4	60V4	85V4
<b>SUPPORT FRAME</b>						
Rubber shoe (width mm)	300	300	400	400	400	450
Attachment points for lifting-anchoring-towing and lubrication of the swing cylinder foot	std	std	std	std	std	std
Variable gauge undercarriage (mm) - Backfill blade with extensions	-	1550-1800   1550	-	-	-	-
Steel shoe (width mm)	300 opt	300 opt	400 opt	400 opt	400 opt	450
<b>ENGINE</b>						
Two-phase dry air filter with visual clogging indicator	std	std	std	std	std	std
Electric pre-heating device	std	std	std	std	std	std
Fuel water separator	std	std	std	std	std	std
Fuel tank with drain plug	plastic material	plastic material	plastic material	plastic material	plastic material	steel
Engine speed adjustment	std	std	std	std	std	std
Auto-Idle and Eco-Mode (fuel consumption reduction)	std	std	std	std	std	std
<b>ELECTRICAL SYSTEM</b>						
12V battery with fuse box	std	std	std	std	std	std
<b>DRIVING SEAT</b>						
Longitudinal adjustment bucket seat, vinyl covering	std	std	std	std	std	std
Fabric seat	opt	opt	opt	opt	opt	std
Non-slip rubber mat	std	std	std	std	std	std
Wrist support	std	std	std	std	std	std
Seatbelt	with reel	with reel	with reel	with reel	with reel	with reel
High speed control	std	std	std	std	std	std
Travel control pedals	std	std	std	std	std	std
<b>EQUIPMENT AND MONITORING DEVICES</b>						
Worklight switch; auxiliary system control	std	std	std	std	std	std
Aux. system proportional control switch on joystick	std	std	std	std	std	std
Water temperature control instrument	analogue	analogue	analogue	analogue	analogue	analogue
Fuel level control instrument	analogue	analogue	analogue	analogue	analogue	analogue
Hour meter	std	std	std	std	std	std
Warning light for: preheating, engine oil pressure, battery charge, water temperature	std	std	std	std	std	std
High speed indicator light	std	std	std	std	std	std
Engine alarm device in case of overheating or low oil pressure	std	std	std	std	std	std
<b>CANOPY VERSION</b>						
FOPS protection against falling objects	std	std	std	std	std	std
TOPS and ROPS protection against tipping and rolling	std	std	std	std	std	std
<b>CABIN VERSION</b>						
TOPS / ROPS protection against tipping / rolling	std	std	std	std	std	std
FOPS protection against falling objects	opt	opt	opt	opt	opt	opt
Heating with fan	std	std	std	std	std	std
Front sliding window under the roof	std	std	std	std	std	std
Removable lower front window	std	std	std	std	std	std
Right-hand side sliding window	std	std	std	std	std	std
Grab handles and "full wide" door handle to facilitate closing from the inside	std	std	std	std	std	std
Radio pre-arrangement	std	std	std	std	std	std
Windscreen wiper and washer on front window	std	std	std	std	std	std
Rearview mirrors (right and left) kit for cabin	opt	opt	opt	opt	opt	opt
Back-up alarm	opt	opt	opt	opt	opt	opt
<b>HYDRAULIC SYSTEM</b>						
ISO assisted hydraulic controls	std	std	std	std	std	std
Pump gear / variable flow rate (std)	std	std	std	std	std	std
Hydraulic arm swing control	pedal	pedal	pedal	pedal	pedal	pedal
Track adjustment control	-	std	-	-	-	-
Worklight positioned centrally on the boom	std	std	std	std	std	std
<b>DIGGING AND MOVING EQUIPMENT</b>						
Boom (length mm)	2250	2450	2700	2700	2900	3150
Arm (length mm)	1200	1280	1350	1600	1600	1780
Long arm	+300mm (opt)	+300mm (opt)	+250mm (opt)	+250mm (opt)	+250mm (opt)	+300mm (opt)
Arm hydraulic swinging angle	140°	140°	140°	140°	140°	130°
Limit shock absorber on boom cylinder	std	std	std	std	std	std
Limit shock absorber on arm cylinder	std	std	std	std	std	std
Rapid attachment of mechanical accessories	opt	opt	opt	opt	opt	opt
Bucket in various dimensions	opt	opt	opt	opt	opt	opt
Loads handling device	opt	opt	opt	opt	opt	opt
<b>HYDRAULIC CIRCUITS FOR ACCESSORIES</b>						
Hydraulic circuit for hammer with direct return to tank for double-acting accessories	std	std	std	std	std	std
Second hydraulic circuit for double-acting accessories	opt	opt	opt	opt	opt	opt
Third hydraulic circuit for double-acting accessories	opt	opt	opt	opt	opt	opt
<b>SAFETY AND COMFORT</b>						
Operating and travel controls lock out to enable the operator to exit	std	std	std	std	std	std
Manual lock for the operating and travel controls	std	std	std	std	std	std
Diesel tank cap with lock and mesh filter	std	std	std	std	std	std
Glass breaker hammer in the cabin	std	std	std	std	std	std
Turret lock automatic brake	std	std	std	std	std	std
Boom cylinder anti-drift system	std	std	std	std	std	std
Horn	std	std	std	std	std	std
Air conditioning for the cabin	opt	opt	opt	opt	opt	std
Rear internal balance weight	-	opt	-	-	-	-
Rear balance weight	opt	-	opt	std	-	std